



AIS Engines Warranty Guidelines

INSTALLATION:

1. Engine coolant system and external oil coolers – professionally cleaned or replaced with new (Required for warranty).
2. Intake system inspected and new air filters installed.
3. Coolant new 50/50 mix.

DAILY:

1. Engine cooling system level – Checked.
2. Engine oil level – Checked.

INITIAL 250 HRS. SERVICE:

1. Engine valve lash adjustment (Required for warranty) sheet filled out and sent back to AIS
2. Engine oil and filter – changed with OEM filter.
3. Engine oil sample (Required for warranty) – Taken and sent back to AIS Engines.
4. Engine coolant sample (Required for warranty) – Taken and sent back to AIS Engines.

EVERY 250 HRS. SERVICE:

1. Engine oil and filter and secondary fuel filters – Changed with OEM filters.
2. Engine oil sample – Taken for customer records.

EVERY 500 HRS. SERVICE:

1. Fuel system primary filters – Replace and inspect with OEM filters.
2. Engine crankcase breathers – Clean or replace.

EVERY 2500 HRS. SERVICE:

1. Engine valve lash adjustment (Required for warranty) – check and adjust as necessary.
2. Engine valve rotators – inspected.

EVERY 3000 HRS. SERVICE:

1. Engine primary and secondary air filters – Change with OEM filters.
2. Engine cooling system fluid – Change.
3. Engine mounts and vibration dampers – Inspected.

All engine modifications VOID warranty (ECM codes, HP settings, EGR blocked off, etc.)

Customer Signature _____ Date _____